

Если вы видите что-то необычное, просто сообщите мне.

Tinode Instant Messaging Server

<https://github.com/tinode/chat>

по быстрому развернуть:

```
# Reference configuration for a simple Tinode server.
# Includes:
# * Mysql database
# * Tinode server
# * Tinode exporters

version: '3.8'

# Base Tinode template.
x-tinode:
  &tinode-base
  depends_on:
    - db
  image: tinode/tinode:latest
  restart: always

x-tinode-env-vars: &tinode-env-vars
  "STORE_USE_ADAPTER": "mysql"
  "PPROF_URL": "/pprof"
  # You can provide your own tinode config by setting EXT_CONFIG env var and binding your
  configuration file to
  # "EXT_CONFIG": "/etc/tinode/tinode.conf"
  "WAIT_FOR": "mysql:3306"
  # Push notifications.
  # Modify as appropriate.
  # Tinode Push Gateway configuration.
```

```
"TNPg_PUSH_ENABLED": "false"
# "TNPg_USER": "<user name>"
# "TNPg_AUTH_TOKEN": "<token>"
# FCM specific server configuration.
"FCM_PUSH_ENABLED": "false"
# "FCM_CRED_FILE": "<path to FCM credentials file>"
# "FCM_INCLUDE_ANDROID_NOTIFICATION": false
#
# FCM Web client configuration.
"FCM_API_KEY": "AIzaSyD6X4ULR-RUsobvs1zZ2bHdJuPz39q2tbQ"
"FCM_APP_ID": "1:114126160546:web:aca6ea2981feb81fb44dfb"
"FCM_PROJECT_ID": "tinode-1000"
"FCM_SENDER_ID": 114126160546
"FCM_VAPID_KEY":
"BOgQVPOMzIMXUpsYGpbVkJZoEBc0ifKY_f2kSU5DNDGYI6i6CoKqxxDd7w7PJ3FaGRBgVGJffldETum0x831jl58"
"FCM_MEASUREMENT_ID": "G-WNJDQR34L3"
# iOS app universal links configuration.
# "IOS_UNIV_LINKS_APP_ID": "<ios universal links app id>"
# Video calls
"WEBRTC_ENABLED": "false"
# "ICE_SERVERS_FILE": "<path to ICE servers config>"

x-exporter-env-vars: &exporter-env-vars
"TINODE_ADDR": "http://tinode.host:6060/stats/expvar/"
# InfluxDB configuration:
"SERVE_FOR": "influxdb"
"INFLUXDB_VERSION": 1.7
"INFLUXDB_ORGANIZATION": "<your organization>"
"INFLUXDB_PUSH_INTERVAL": 30
"INFLUXDB_PUSH_ADDRESS": "https://mon.tinode.co/intake"
"INFLUXDB_AUTH_TOKEN": "<auth token>"
# Prometheus configuration:
# "SERVE_FOR": "prometheus"
# "PROM_NAMESPACE": "tinode"
# "PROM_METRICS_PATH": "/metrics"

services:
  db:
    image: mysql:8.0
    container_name: mysql
    restart: always
```

```
# Use your own volume.
# volumes:
# - <mysql directory in your file system>:/var/lib/mysql
environment:
  - MYSQL_ALLOW_EMPTY_PASSWORD=yes
healthcheck:
  test: ["CMD", "mysqladmin" ,"ping", "-h", "localhost"]
  timeout: 5s
  retries: 10
security_opt:
  - seccomp=unconfined

# Tinode.
tinode-0:
  << : *tinode-base
  container_name: tinode-0
  hostname: tinode-0
  # You can mount your volumes as necessary:
  # volumes:
  # # E.g. external config (assuming EXT_CONFIG is set).
  # - <path to your tinode.conf>:/etc/tinode/tinode.conf
  # # Logs directory.
  # - <path to your tinode-0 logs directory>:/var/log
ports:
  - "6060:6060"
environment:
  << : *tinode-env-vars
  "RESET_DB": ${RESET_DB:-false}
  "UPGRADE_DB": ${UPGRADE_DB:-false}

# Monitoring.
# Exporters are paired with tinode instances.
exporter-0:
  container_name: exporter-0
  hostname: exporter-0
  depends_on:
    - tinode-0
  image: tinode/exporter:latest
  restart: always
ports:
  - "6222:6222"
```

links:

- tinode-0:tinode.host

environment:

<< : *exporter-env-vars

"WAIT_FOR": "tinode-0:6060"

Revision #1

Created 2026-04-16 09:06:07 UTC by gasick

Updated 2026-04-16 09:06:54 UTC by gasick